

Spannlager Reihe FBB762.2RSR

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]	
	FAG	FBB203 + 76203/12.2RSR	-	-	-	-	-	-	-	-	k.F.
	SKF	PFT 40 + 1726201-2RS1	-	-	-	-	-	-	-	-	k.F.
	INA		-	-	-	-	-	-	-	-	k.F.
12	RHP	(Gehäuse k.A.) 1726201-2RS	81	4	58,7	13,4	63,5	7,1	49	M6	
	NSK		-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	k.F.
	NBR		-	-	-	-	-	-	-	-	k.F.
	FYH		-	-	-	-	-	-	-	-	k.F.
	NTN		-	-	-	-	-	-	-	-	k.F.
	ISO 3228	Table5/Figure5 (oval)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6	
	DIN 626-2	EBY 203 (Lager k.A.)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6	

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]	
	FAG	FBB203 + 76203/15.2RSR	-	-	-	-	-	-	-	-	k.F.
	SKF		-	-	-	-	-	-	-	-	k.F.
	INA		-	-	-	-	-	-	-	-	k.F.
	RHP	(Gehäuse k.A.) 1726202-2RS	81	4	58,7	13,4	63,5	7,1	49	M6	
15	NSK		-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	k.F.
	NBR		-	-	-	-	-	-	-	-	k.F.
	FYH		-	-	-	-	-	-	-	-	k.F.
	NTN		-	-	-	-	-	-	-	-	k.F.
	ISO 3228	Table5/Figure5 (oval)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6	
	DIN 626-2	EBY 203 (Lager k.A.)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6	

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]		
17	FAG	FBB203 + 76203.2RSR	82	4,5	60	15	63,5	7,1	50	M6		
	SKF	PFT 40 + 1726203-2RS1	81	4	59	14	63	7,1	49	M6		
	INA	FLAN 03.40 MST + 203 NPPB	81	4	58,7	14	63,5	7,1	48	M6		
	RHP	(Gehäuse k.A.) 1726203-2RS	81	4	58,7	13,4	63,5	7,1	49	M6		
	NSK	PFL 203 + CS 203 DDU	81	4	59	14	63,5	7	49	M6		
	HFH		-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSPFL 203 PFL 203 + CS 203	81	4	59	14	63	7	49	M6		
	FYH	PFL 203 + SC 203	81	4	59	14	63,5	7,5	-	M6		
	NTN	PFL203 + CS203LLU	81	4	59	14	63,5	7,1	49	M6		
	ISO 3228	Table5/Figure5 (oval)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6		
	DIN 626-2	EBY 203 (Lager k.A.)	max 82	max 4,5	max 60	max 15	63,5	7,1	-	M6		

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]		
20	FAG	FBB204 + 76204.2RSR	91	4,5	68	17	71,5	9	57	M8		
	SKF	PFT 47 + 1726204-2RS1	91	4	67	16	71,5	8,7	55	M8		
	INA	FLAN 03.47 MST + 204 NPPB	90,5	4	66	16	71,5	8,7	55	M8		
	RHP	(Gehäuse k.A.) 1726204-2RS	90,5	4	66,7	15,4	71,5	8,7	55	M8		
	NSK	PFL 204 + CS 204 DDU	90	4	67	16	71,4	9	56	M8		
	HFH		-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSPFL 204 PFL 204 + CS 204	90	4,5	67	16	71	9	56	M8		
	FYH	PFL 204 + SC 204	90	4	67	17	71,5	9	-	M8		
	NTN	PFL204 + CS204LLU	90	4	67	16	71,5	9	56	M8		
	ISO 3228	Table5/Figure5 (oval)	max 91	max 4,5	max 68	max 17	71,5	9	-	M8		
	DIN 626-2	EBY 204 (Lager k.A.)	max 91	max 4.5	max 68	max 17	71,5	9	-	M8		

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]		
25	FAG	FBB205 + 76205.2RSR	96	4,5	72	19	76	9	62	M8		
	SKF	PFT 52 + 1726205-2RS1	95	4	71	18	76	8,7	60	M8		
	INA	FLAN 03.52 MST + 205 NPPB	95,2	4	71	17,4	76	8,7	60	M8		
	RHP	(Gehäuse k.A.) 1726205-2RS	95,3	4	71	17,4	76	8,7	60	M8		
	NSK	PFL 205 + CS 205 DDU	95	4	71	18	76,2	9	60	M8		
	HFH		-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSPFL 205 PFL 205 + CS 205	95	4,5	71	18	76	9	60	M8		
	FYH	PFL 205 + SC 205	95	4	71	20	76	9	-	M8		
	NTN	PFL205 + CS205LLU	95	4	71	18	76	9	60	M8		
	ISO 3228	Table5/Figure5 (oval)	max 96	max 4,5	max 72	max 19	76	9	-	M8		
	DIN 626-2	EBY 205 (Lager k.A.)	max 96	max 4,5	max 72	max 19	76	9	-	M8		

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]		
30	FAG	FBB206 + 76206.2RSR	114	5,5	85	20	90,5	11	73	M10		
	SKF	PFT 62 + 1726206-2RS1	112	5	84	19	90,5	10,5	71	M10		
	INA	FLAN 03.62 MST + 206 NPPB	112,7	5	84	17,4	90,5	10,5	71	M10		
	RHP	(Gehäuse k.A.) 1726206-2RS	112,7	5	84,1	18	90,5	10,5	71	M10		
	NSK										k.F.	
	HFH		-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSPFL 206 PFL 206 + CS 206	113	5,5	84	18	90,5	11	71	M10		
	FYH	PFL 206 + SC 206	113	5,2	84	23	90	10,5	-	M10		
	NTN	PFL206 + CS206LLU	113	5,2	84	18	90,5	11	71	M10		
	ISO 3228	Table5/Figure5 (oval)	max 114	max 5,5	max 85	max 20	90,5	11	-	M10		
	DIN 626-2	EBY 206 (Lager k.A.)	max 114	max 5,5	max 85	20	90,5	11	-	M10		

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]	
35	FAG	FBB207 + 76207.2RSR	127	5,5	95	23	100	11	83	M10	
	SKF	PFT 72 + 1726207-2RS1	122	5	94	20	100	11	81	M10	
	INA	FLAN 03.72 MST + 207 NPPB	123	5	93,7	21	100	10,5	81	M10	
	RHP	(Gehäuse k.A.) 1726207-2RS	-	-	-	-	-	-	-	-	k.F.
	NSK										k.F.
	HFH		-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	k.F.
	NBR	CSPFL 207 PFL 207 + CS 207	122	5,5	94	20	100	11	81	M10	
	FYH	PFL 207 + SC 207	-	-	-	-	-	-	-	-	k.F.
	NTN	PFL207 + CS207LLU	122	5,2	94	20	100	11	81	M10	
	ISO 3228	Table5/Figure5 (oval)	max 127	max 5,5	max 95	23	100	11	-	M10	
	DIN 626-2	EBY 207 (Lager k.A.)	max 127	max 5,5	max 95	23	100	11	-	M10	

Welle Ø [mm]	Hersteller	Bezeichnung	a max [mm]	c max [mm]	D1 max [mm]	g max [mm]	m [mm]	u max [mm]	x min [mm]	s [mm]		
40	FAG	FBB208 + 76208.2RSR	-	-	-	-	-	-	-	-	k.F.	
	SKF	PFT 80 + 1726208-2RS1	148	7	104	20	119	13,5	91	M12		
	INA	FLAN 03.80 MST + 208 NPPB	148	7	100	23	119	13,5	90	M12		
	RHP	(Gehäuse k.A.) 1726208-2RS	-	-	-	-	-	-	-	-	k.F.	
	NSK		-	-	-	-	-	-	-	-	k.F.	
	HFH		-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	k.F.	
	NBR	CSPFL 208 PFL 208 + CS 208	148	7	100	24	119	14	90	M12		
	FYH	PFL 208 + SC 208	-	-	-	-	-	-	-	-	k.F.	
	NTN	PFL208 + CS208LLU	148	6,8	100	21	119	13,5	91	M12		
	ISO 3228	Table5/Figure5 (oval)	-	-	-	-	-	-	-	-	-	k.F.
	DIN 626-2	EBY 208 (Lager k.A.)	max 149	max 7	max 104	23	119	13,5	-	M12		