

Spannlager Reihe P762.2RSR

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s	
12	FAG	P76203/12.2RSR P203 + 76203/12.2RSR	125	32	13	30,2	57	96	-	11,5	16	M10	k.F.
	SKF	SY 503 M + 1726201-2RS1	127	32	14	30,2	56	88	106	11,5	20,5	M10	k.F.
	INA	GG ASE 03 + 201 NPPB	125	30	10	30,2	57	95	-	11	19	M10	
	RHP	NP12-2RS (Gehäuse k.A.) 1726201-2RS	126,5	30,5	14,2	30,2	57,2	85,5	100,5	-	-	M10	
	NSK	-	-	-	-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.
	NBR												k.F.
	FYH												k.F.
	NTN												k.F.
		ISO 3228	Figure 1/Table 1 k.A.	max 129	max 39	max 17	30,2	-	96	-	min 10,5 max 12,43	min 16	M10
	DIN 626-2	k. A. SGY 203 (Lager k.A.)	max 129	max 39	max 17	30,2	-	96	-	min 10,5 max 12,5	min 16	M10	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
15	FAG	P76203/15.2RSR P203 + 76203/15.2RSR	125	32	13	30,2	57	96	-	11,5	16	M10	k.F.	
	SKF	SY 503 + 1726202-2RS1	127	32	14	30,2	56	88	106	11,5	20,5	M10	k.F.	
	INA	GG ASE 03 + 202 NPPB	125	30	10	30,2	57	95	-	11	19	M10		
	RHP	NP15-2RS (Gehäuse k.A.) 1726202-2RS	126,5	30,5	14,2	30,2	57,2	85,5	100,5	-	-	M10		
	NSK								-				k.F.	
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.	
	NBR												k.F.	
	FYH												k.F.	
	NTN												k.F.	
		ISO 3228	Figure1/Table1 k.A.	max 129	max 39	max 17	30,2	-	96	-	in 10,5 max 12,4	min 16	M10	
		DIN 626-2	SGY 203 (Lager k.A.)	max 129	max 39	max 17	30,2	-	96	-	in 10,5 max 12,4	min 16	M10	

Welle ø [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
17	FAG	P76203.2RSR P203 + 76203.2RSR	125	32	13	30,2	57	96	-	11,5	16	M10	k.F.	
	SKF	SY 503 + 1726203-2RS1	127	32	14	30,2	57	96	-	11,5	20,5	M10		
	INA	GG ASE 03 + 203 NPPB	125	30	10	30,2	57	95	-	11	19	M10		
	RHP	NP17-2RS (Gehäuse k.A.) 1726203-2RS	126,5	30,5	14,2	30,2	57,2	85,5	100,5	-	-	M10		
	NSK								-				k.F.	
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.	
	NBR												k.F.	
	FYH												k.F.	
	NTN												k.F.	
		ISO 3228	Figure1/Table1 k.A.	max 129	max 39	max 17	30,2	-	96	-	in 10,5 max 12,4	min 16	M10	
		DIN 626-2	k. A. SGY 203 (Lager k.A.)	max 129	max 39	max 17	30,2	-	96	-	in 10,5 max 12,4	min 16	M10	

Welle ø [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
20	FAG	P76204.2RSR P204 + 76204.2RSR	127	38	14	33,3	65	95	-	11,5	16	M10	k.F.	
	SKF	SY 504 M + 1726204-2RS1	127	32	14	33,3	65	96	-	11,5	20,5	M10		
	INA	GG ASE 04 + 204 NPPB	130	32	14,5	33,3	64	97	-	11	19	M10		
	RHP	NP20-2RS (Gehäuse k.A.) 1726204-2RS	127	32,5	14	33,3	65,2	88,5	100,5	-	-	M10		
	NSK	P 204 + CS 204 DDU	127	38	15	33,3	65	95	-	13	19	M10		
	HFH		-	-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSP 204 P 204 + CS 204	127	38	13	33,3	65	95	-	13	19	M10		
	FYH	P 204 + SC 204	127	38	13	33,3	64	95	-	13	16	M10		
	NTN	P204 + CS204LLU	127	38	14	33,3	65	95	-	13	16	M10		
	ISO 3228	Figure1/Table1 k.A.	max 134	max 39	max 17	33,3	-	96	-	in 10,5 max 12,4	min 16	M10		
	DIN 626-2	k. A. SGY 204 (Lager k.A.)	max 134	max 39	max 17	33,3	-	96	-	in 10,5 max 12,4	min 16	M10		

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
25	FAG	P76205.2RSR P205 + 76205.2RSR	140	38	15	36,5	71	105	-	11,5	16	M10	k.F.	
	SKF	SY 505 M + 1726205-2RS1	130	36	16	36,5	70,5	105	-	11,5	19,5	M10		
	INA	GG ASE 05 + 205 NPPB	130	36	14,5	36,5	70	103	-	11	19	M10		
	RHP	NP25-2RS (Gehäuse k.A.) 1726205-2RS	139	36,5	16	36,5	71	112,7	96,8	-	-	M10		
	NSK	P 205 + CS 205 DDU	140	38	16	36,5	70	105	-	13	19	M10		
	HFH		-	-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSP 205 P 205 + CS 205	140	38	13	36,5	71	105	-	13	19	M10		
	FYH	P 205 + SC 205	140	38	13	36,5	71	105	-	13	19	M10		
	NTN	P205 + CS205LLU	140	38	15	36,5	71	105	-	13	16	M10		
	ISO 3228	Figure1/Table1 k.A.	max 142	max 39	max 17	36,5	-	105	-	min 10,5 max 12,4	min 16	M10		
	DIN 626-2	k. A. SGY 205 (Lager k.A.)	max 142	max 39	max 17	36,5	-	105	-	min 10,5 max 12,4	min 16	M10		

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
30	FAG	P76206.2RSR P206 + 76206.2RSR	165	48	17	42,9	83	121	-	14	19	M12		
	SKF	SY 506 M + 1726206-2RS1	152	40	17	42,9	82,5	121	-	14	23,5	M12		
	INA	GG ASE 06 + 206 NPPB	158	40	17	42,9	82	118	-	14	22	M12		
	RHP	NP30-2RS (Gehäuse k.A.) 1726206-2RS	160,5	41,5	17,7	42,9	82,7	129,5	108,5	-	-	M12		
	NSK		-	-	-	-	-	-	-	-	-	-	k.F.	
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.	
	NBR	CSP 206 P 206 + CS 206	165	48	15	42,9	84	121	-	17	21	M14		
	FYH	P 206 + SC 206	165	48	15	42,9	84	121	-	17	21	M14		
	NTN	P206 + CS206LLU	165	48	17	42,9	83	121	-	17	20	M14		
		ISO 3228	Figure1/Table1 k.A.	max 167	max 48	max 20	42,9	-	121	-	min 13 max 14,9	min 19	M12	
		DIN 626-2	SGY 206 (Lager k.A.)	max 167	max 48	max 20	42,9	-	121	-	min 13 max 15	min 19	M12	

Welle ø [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s	
	FAG	P76207.2RSR P207 + 76207.2RSR	167	48	18	47,6	93	126		14	19	M12	
	SKF	SY 507 M + 1726207-2RS1	160	45	19	47,6	93	126	-	14	21	M12	
	INA	GG ASE 07 + 207 NPPB	163	45	19	47,6	93	126		14	21	M12	
	RHP	NP35-2RS (Gehäuse k.A.) 1726207-2RS	166	44,5	17,5	47,6	93	136,5	121,5			M12	
35	NSK		-	-	-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.
	NBR	CSP 207 P 207 + CS 207	167	48	16	47,6	93	127		17	21	M14	
	FYH	P 207 + SC 207	167	48	16	47,6	93	127		17	21	M14	
	NTN	P207 + CS207LLU	167	48	18	47,6	93	127		17	20	M14	
	ISO 3228	Figure1/Table1 k. A.	max 172	max 48	max 20	47,6		126		min 13 max 14,9	min 19	M12	
	DIN 626-2	k. A. SGY 207 (Lager k.A.)	max 172	max 48	max 20	47,6		126		min 13 max 15	min 19	M12	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
40	FAG	P76208.2RSR P208 + 76208.2RSR	184	54	18	49,2	98	136	-	14	19	M12		
	SKF	SY 508 M + 1726208-2RS1	175	48	19	49,2	99	136	-	14	21	M12		
	INA	GG ASE 08 + 208 NPPB	179	48	19	49,2	99	138	-	14	21	M12		
	RHP	NP40-2RS (Gehäuse k.A.) 1726208-2RS	180,5	51	18,5	49,2	98,5	148	127	-	-	M12		
	NSK		-	-	-	-	-	-	-	-	-	-	k.F.	
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.	
	NBR	CSP 208 P 208 + CS 208	184	54	17	49,2	98	137	-	17	21	M14		
	FYH		-	-	-	-	-	-	-	-	-	-	k.F.	
	NTN	P208 + CS208LLU	184	54	18	49,2	98	137	-	17	20	M14		
		ISO 3228	Figure1/Table1 k.A.	max 186	max 55	max 20	49,2	-	136	-	min 13 max 14,9	min 19	M12	
		DIN 626-2	k.A. SGY 208 (Lager k.A.)	max 186	max 55	max 20	49,2	-	136	-	min 13 max 15	min 19	M12	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s		
45	FAG	P76209.2RSR P209 + 76209.2RSR	190	54	20	54	106	146	-	14	19	M12		
	SKF	SY 509 M + 1726209-2RS1	187	48	21	54	107,5	146	-	14	22,5	M12		
	INA	GG ASE 09 + 209 NPPB	192	48	21,5	54	107	150	-	14	21	M12		
	RHP	NP45-2RS (Gehäuse k.A.) 1726209-2RS	190,5	54	20	54	108	154,5	140,5	-	-	M12		
	NSK		-	-	-	-	-	-	-	-	-	-	k.F.	
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.	
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.	
	NBR		-	-	-	-	-	-	-	-	-	-	k.F.	
	FYH		-	-	-	-	-	-	-	-	-	-	k.F.	
	NTN	P209 + CS209LLU											k.F.	
		ISO 3228	Figure1/Table1 k.A.	max 192	max 55	max 22	54	-	146	-	min 13 max 14,9	min 19	M12	
		DIN 626-2	k.A. SGY 209 (Lager k.A.)	max 192	max 55	max 22	54	-	146	-	min 13 max 15	min 19	M12	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s	
50	FAG	P76210.2RSR P210 + 76210.2RSR	206	60	21	57,2	114	159	-	18	20,5	M16	
	SKF	SY 510 M + 1726210-2RS1	203	54	22	57,2	114,5	159	-	18	26	M16	
	INA	GG ASE 10 + 210 NPPB	200	54	21,5	57,2	115	158	-	18	23	M16	
	RHP	NP50-2RS (Gehäuse k.A.) 1726210-2RS	-	-	-	-	-	-	-	-	-	-	k.F.
	NSK		-	-	-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.
	NBR		-	-	-	-	-	-	-	-	-	-	k.F.
	FYH		-	-	-	-	-	-	-	-	-	-	k.F.
	NTN	P210 + CS210LLU											k.F.
	ISO 3228	Figure1/Table1 k.A.	max 208	max 61	max 23	57,2	-	159	-	min 17 max 19,0	min 20,5	M16	
	DIN 626-2	k.A. SGY 210 (Lager k.A.)	max 208	m	max 23	57,2	-	159	-	min 17 max 19	min 20,5	M16	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s	
55	FAG	P76211.2RSR P211 + 76211.2RSR	219	60	23	63,5	126	171	-	18	20,5	M16	
	SKF		-	-	-	-	-	-	-	-	-	-	k.F.
	INA		-	-	-	-	-	-	-	-	-	-	k.F.
	RHP		-	-	-	-	-	-	-	-	-	-	k.F.
	NSK		-	-	-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.
	NBR		-	-	-	-	-	-	-	-	-	-	k.F.
	FYH		-	-	-	-	-	-	-	-	-	-	k.F.
	NTN		-	-	-	-	-	-	-	-	-	-	k.F.
	ISO 3228	Figure1/Table1 k.A.	max 233	max 61	max 25	63,5	-	172	-	min 17 max 19,0	min 20,5	M16	
	DIN 626-2	k. A. SGY 211 (Lager k.A.)	max 233	max 61	max 25	63,5	-	172	-	min 17 max 19	min 20,5	M16	

Welle ϕ [mm]	Hersteller	Bezeichnung	a [mm]	b [mm]	c [mm]	h [mm]	h1 [mm]	m (max) [mm]	m (min) [mm]	u [mm]	v [mm]	s	
	FAG	P76212.2RSR P212 + 76212.2RSR	241	70	25	69,9	138	184	-	18	22	M16	
	SKF		-	-	-	-	-	-	-	-	-	-	k.F.
	INA		-	-	-	-	-	-	-	-	-	-	k.F.
	RHP		-	-	-	-	-	-	-	-	-	-	k.F.
60	NSK		-	-	-	-	-	-	-	-	-	-	k.F.
	HFH		-	-	-	-	-	-	-	-	-	-	k.F.
	ASAHI		-	-	-	-	-	-	-	-	-	-	k.F.
	NBR		-	-	-	-	-	-	-	-	-	-	k.F.
	FYH		-	-	-	-	-	-	-	-	-	-	k.F.
	NTN		-	-	-	-	-	-	-	-	-	-	k.F.
	ISO 3228	Figure1/Table1 k.A.	max 243	max 71	max 27	69,9	-	186	-	min 17 max 19,0	min 22	M16	
	DIN 626-2	k.A. SGY 212 (Lager k.A.)	max 243	max 71	max 27	69,9	-	186	-	min 17 max 19	min 22	M16	